


LAH2 系列




类别		时间继电器 Time Relay		
型号		LAH2-N	LAH2-Y	
外形尺寸 (毫米)		61.0H × 49.0W × 82.0L	88.0H × 58.0W × 82.0L	
时间范围		SEC:1,3,6,10,12,30,60 MIN:3,6,10,30,60 HR:3,6,10,24		
额定电压		AC:12V-24V-110/220V-380V-415V-440V 50/60Hz DC:12V-24V-48V		
指示灯动作		ON, UP指示		
O/P输出接点	型号	AH2-N1/AH2-Y1	AH2-N2/AH2-Y2	AH2-N/AH2-Y
	限时 1C	5A		5A
	限时 2C		5A	
	瞬时 1C			5A
寿命	机械	5 × 10 <sup>6</sup> Times		
	电气	10 <sup>5</sup> Times		
精确度	往复误差	± 1% max.		
	设定误差	± 10% max		
	电压误差	± 1% max.		
	温度误差	± 2% max.		
复位时间		0.1sec max.		
消耗功率		3VA		
使用周围温度		-10 ~+50		
使用周围湿度		48~85%RH		
重量		220g		
安装于其底座	露出型			US-08 P3G-08
	埋入型	8PFA		


LAH2 安装尺寸和接线、时序图



LAH2-Y1, LAH2-N1



LAH2-Y2, LAH2-N2



LAH2-Y, LAH2-N

