


LST3P 系列






类别	断电时间继电器		星三角时间继电器		
型号	LST3PF	LST3PK	LST3PY		
外形尺寸 (毫米)	55.0H x 40.5W x 84.0L			55.0H x 40.5W x 84.0L	
时间范围	0.1~1s	2.5~30s	1~10s		
	0.5~5s	5~60s	2~30s		
	1~10s	15~180s	5~60s		
额定电压	AC:12V-24V-48V-110V-220V 50/60HZ DC:12V-24V-48V-110			AC110/220V	
指示灯动作	通电指示			Y- 指示	
O/P输出接点	型号	LST3PF	LST3PF(T1)	LST3PFK	LST3PY
	限时 1C	5A		3A(5A)	3A
	限时 2C		3A(5A)		
	瞬时 1C				
寿命	机械	5 x 10 <sup>7</sup> Times			5 x 10 <sup>7</sup> Times
	电气	10 <sup>4</sup> Times			2 x 10 <sup>4</sup> Times
精确度	往复误差	± 2% max.			± 2% max.
	设定误差	± 5% max.			± 5% max.
	电压误差	± 5% max.			± 5% max.
	温度误差	± 2% max.			± 2% max.
复位时间	0.1sec max.			0.1sec max.	
消耗功率	2.5VA			3VA	
使用周围温度	-10 ~+50			-10 ~+50	
使用周围湿度	35~85%RH			35~85%RH	
重量	100g			180g	
安装于其底座	露出	PF083A 8PFA			PF083A 8PFA
	埋入型	Y-40 & US-08 or Y-40 & P3G-08			Y-40 & US-08 or Y-40 & P3G-08



安装尺寸和接线、时序图






LST3PF



LST3PF(T1)



LST3PK



LST3PY

