


## LST3P 系列






|           |   |   |        |        |
|-----------|---|---|--------|--------|
| 类别        | 多段式时间继电器  |   |        |        |
| 型号        | LST3PA  | LST3PC  | LST3PG |        |
| 外形尺寸 (毫米) | 55.0H x 40.5W x 84.0L   |   |        |        |
| 时间范围      | A:0.05-0.5s/5s/30s/3min<br>B:0.1-1s/10s/60s/6min<br>C:0.5-5s/50s/5min/30min<br>D:1-10s/100s/10min/60min | E:5-60s/10min/60min/6h<br>F:0.25-2min/20min/2h/12h<br>G:0.5-5min/40min/4h/24h |        |        |
| 额定电压      | AC:12V-24V-48V-110V-220V-380V 50/60HZ DC:12V-24V-48V-110  |   |        |        |
| 指示灯动作     | ON, UPG两只指示灯  |   |        |        |
| O/P输出接点   | 型号  | LST3PA  | LST3PC | LST3PG |
|           | 限时 1C   |   | 5A     |        |
|           | 限时 2C   | 5A(10A)   |        | 5A     |
| 寿命        | 瞬时 1C   |   | 5A     |        |
|           | 机械  | 5 x 10 <sup>7</sup> Times   |        |        |
| 精确度       | 电气  | 10 <sup>6</sup> Times   |        |        |
|           | 往复误差  | ± 2% max.   |        |        |
|           | 设定误差 S  | ± 5% max.   |        |        |
|           | 电压误差  | ± 5% max.   |        |        |
| 复位时间      | 温度误差  | ± 2% max.   |        |        |
|           |   | 0.1sec max.   |        |        |
| 消耗功率      | 3VA   |   |        |        |
| 使用周围温度    | -10 ~+50  |   |        |        |
| 使用周围湿度    | 35~85%RH  |   |        |        |
| 重量        | 100g  |   |        |        |
| 安装于其底座    | 露出  | PF083A 8PFA   |        |        |
|           | 埋入型   | Y-40 & US-08 or Y-40 & P3G-08   |        |        |




### 安装尺寸和接线、时序图



LST3PA



LST3PC



LST3PG

