

LJQX-15F Series



Model	LJQX-15F(T90)		LJQX-16F(T91)	
Dimension(mm)	32×26.5×18.7		32×26.5×27.9	
Contact Form	1Z 1H 1D			
Contact Material	Silver alloy			
Resistance Performance Of Contactor Capacity	30A/40A/28VDC 30A/40A/250VAC			
Coil Power at 23℃	DC(W)	≤0.9W		
	AC(VA)	/		
Coil Voltage	DC(V)	6~48V		
	AC(V)	/		
Pick-up Voltage at 23℃	DC≤75%			
Drop-out Voltage at 23℃	DC≥10%			
Max Voltage at 23℃	110%			
Contact Resistance(at 6VDC 1A)	≤100mΩ			
Dielectric Strength	Between Open Contacts	≥1200VAC 50Hz/1min Leakage current 1mA		
	Contacts pieces	/		
	Between Coil & Contacts	≥1500VAC 50Hz/1min Leakage current 1mA		
Insulation Resistance(MΩ) at 500VDC	≥100MΩ		≥100MΩ	
Service life	Electrical	10 ⁵ Times(Frequency: On1Time/1S, Off1次Time/1S)		
	Mechanical	10 ⁶ Times(Frequency: 300次Time/1min)		
Ambient Temperature	-25℃~+55℃			
Terminal type	Welding type			
Suitable socket	/			
Product Weight	25g		30g	
Same Reference	T90		T91	

LJQX-15F(T90) 、LJQX-16F(T91) Installation dimensions and connecting diagram

