

LJQX、LJTX Series



Model		LJQX-10F	LJTX
Dimension(mm)		34.5×34.5×53	
Contact Form		2Z 2H 2D	3Z 3H 3D
Contact Material		Silver alloy	
Resistance Performance Of Contactor Capacity		5A/28VDC 5A/250VAC	
Coil Power at 23°C	DC(W)	≤2W	
	AC(VA)	≤3.5VA	
Coil Voltage	DC(V)	6~220V	
	AC(V)	6~380V	
Pick-up Voltage at 23°C		DC≤75% AC≤80%	
Drop-out Voltage at 23°C		DC≥10% AC≥30%	
Max Voltage at 23°C		110%	
Contact Resistance(at 6VDC 1A)		≤100mΩ	
Dielectric Strength	Between Open Contacts	≥1200VAC 50Hz/1min Leakage current 1mA	
	Contacts pieces	≥1500VAC 50Hz/1min Leakage current 1mA	
	Between Coil & Contacts	≥1500VAC 50Hz/1min Leakage current 1mA	
Insulation Resistance(MΩ)at 500VDC		≥100MΩ	
Service life	Electrical	10 ⁵ Times(Frequency: On1Time/1S, 断Off1次Time/1S)	
	Mechanical	10 ⁸ Times(Frequency: 300Time/1min)	
Ambient Temperature		-25°C~+55°C	
Terminal type		Insert type	
Suitable socket		LPF083A LPF083A-E LPL08	LPF113A LPF113A-E LPL11
Product Weight		76g	76g
Same Reference			

LJQX-10F、LJTX 安装尺寸和接线图 Installation dimensions and connecting diagram

