

LAH3D□ -□ Series



Classification		Time Relay		
Model		LAH3D2-□	LAH3D3-□	LAH3DM-□
Dimension(mm)		50.0H × 40.5W × 82.0L		
Full Timing Range		9.9S, 99S, 9.9M, 99M, 9.9H, 99H,	99.9S, 999S, 99.9M, 999M, 99.9H, 999H,	0.1S~990H
Rated Voltage		AC:12V-24V-110/220V-380V DC:12V-24V		
Indicator Operating		ON, UP Operating ON, UP		
O/P Contact	Mode	1C Time Limit	2C Time Limit	1C Instantaneous
	-1	5A		
	-2		5A	
	-3	5A		5A
Service life	Mechanical	5 × 10 <sup>6</sup> Times		
	Electrical	10 <sup>5</sup> Times		
Accuracy	Repeat Error	± 1% max.		
	Setting Error	± 10% max		
	Voltage Error	± 1% max.		
	Temp Error	± 2% max.		
Reset Time		0.1sec max.		
Power consumption		2.5VA		
Ambient Temperature		-10°C~+55°C		
Ambient Humidity		48~85%RH		
Weight		160g		
Mounting & Socket	Surface	PF083A 8PFA	US-08 P3G-08	
	Flush	Y-40 & US-08 or Y-40 & P3G-08		

LAH3D□ -□ Installation dimensions and connecting, sequence diagram

