

LAH3-□ Series



Classification		Time Relay		
Model		LAH3-□		
Dimension(mm)		50.0H × 40.5W × 82.0L		
Full Timing Range		SEC:1,3,6,10,12,30,60 MIN:3,6,10,12,30,60 HR:3,6,10,12		
Rated Voltage		AC:12V-24V-110/220V-380V DC:12V-24V		
Indicator Operating		ON, UP Operating ON, UP		
Contact	Model	LAH3-1	LAH3-2	LAH3-3
	1C Time Limit	5A		5A
	2C Time Limit		5A	
	1C Instantaneous			5A
Service life	Mechanical	5 × 10 ⁶ Times		
	Electrical	10 ⁵ Times		
Accuracy	Repeat Error	± 1% max.		
	Setting Error	± 10% max		
	Voltage Error	± 1% max.		
	Temp Error	± 2% max.		
Reset Time		0.1sec max.		
Power consumption		2.5VA		
Ambient Temperature		-10°C~+55°C		
Ambient Humidity		48~85%RH		
Weight		160g		
Mounting & Socket	Surface	PF083A 8PFA	US-08 P3G-08	
	Flush	Y-40 & US-08 or Y-40 & P3G-08		

LAH3-□ Installation dimensions and connecting, sequence diagram

