


LST3P Series






Classification		Multi Range Time Relay		
Model		LST3PA	LST3PC	LST3PG
Dimension(mm)		55.0H × 40.5W × 84.0L		
Full Timing Range		A:0.05-0.5s/5s/30s/3min B:0.1-1s/10s/60s/6min C:0.5-5s/50s/5min/30min D:1-10s/100s/10min/60min	E:5-60s/10min/60min/6h F:0.25-2min/20min/2h/12h G:0.5-5min/40min/4h/24h	
Rated Voltage		AC:12V-24V-48V-110V-220V-380V 50/60HZ DC:12V-24V-48V-110		
Indicator Operating		ON, UP Two Indicator		
O/P Contact	Model	LST3PA	LST3PC	LST3PG
	1C Time Limit		5A	
	2C Time Limit	5A(10A)		5A
	1C Instantaneous		5A	
Service life	Mechanical	5 × 10 ⁷ Times		
	Electrical	10 ⁶ Times		
Accuracy	Repeat Error	±2% max.		
	Setting Error	±5% max.		
	Voltage Error	±5% max.		
	Temp Error	±2% max.		
Reset Time		0.1sec max.		
Power consumption		3VA		
Ambient Temperature		-10°C~+50°C		
Ambient Humidity		35~85%RH		
Weight		100g		
Mounting & Socket	Surface	PF083A 8PFA		
	Flush	Y-40 & US-08 or Y-40 & P3G-08		




Installation dimensions and connecting, sequence diagram



LST3PA



LST3PC



LST3PG

